

### Rotary Hand Pumps continued

#### 7.5 Gallon/100 Strokes

3/4" inlet | Spout outlet  
2" NPT bung mount

Cast iron housing

#### Included Accessories

Compatible with diesel, kerosene, machine oil, fuel oil, petroleum products

S062 N Pail spout, 3-piece steel suction pipe 13" to 39"



# FILL-RITE®

## Accessories For Gasoline / Diesel / B20 / E-15 / Kerosene

### Hoses

Internal spring guard  
Stainless steel ground wire

Fuel-resistant Neoprene exterior  
Suitable for all electric pumps

Available in 1" and 3/4" NPT

#### 1" Models

FRH10012	N	12'   3.6 m
FRH10014	N	14'   4.3 m
FRH10020	N	20'   6 m
FRHA10020	NA	20'   6 m (Rated to -40°F/-40°C)

#### 3/4" Models

FRH07512	N	12'   3.6 m (Pictured right)
FRH07514	N	14'   4.3 m
FRH07520	N	20'   6 m
FRHA07515	NA	15'   4.6 m (Rated to -40°F/-40°C)

### UL listed Models

300F7773	N	1" x 12'   2.5 cm x 3.6 m
700F3135	N	3/4" x 12'   1.9 cm x 3.6 m



### Filters

Particulate, Hydrosorb® & Aqua  
Increase pump longevity

Compatible with gasoline and diesel

F4030PM0	N	Particulate   Up to 40 GPM (151 LPM)   50 PSI (3.4 bar)   30 Micron
F4010PM0	N	Particulate   Up to 40 GPM (151 LPM)   50 PSI (3.4 bar)   10 Micron
F1810PM0	N	Particulate   Up to 18 GPM (68 LPM)   50 PSI (3.4 bar)   10 Micron
F1810PM1	N	Particulate w/ drain   Up to 18 GPM (68 LPM)   50 PSI (3.4 bar)   10 Micron
F1810HM0	N	Hydrosorb   Up to 18 GPM (68 LPM)   50 PSI (3.4 bar)   10 Micron
F1810PC1	N	Particulate w/ drain   Up to 18 GPM (68 LPM)   50 PSI (3.4 bar)   10 Micron
F1810HC1	N	Aqua w/ drain   Up to 18 GPM (68 LPM)   50 PSI (3.4 bar)   10 Micron
1210KTF7019	N	F1810HM0 filter w/ 1200KTS9075 filter head kit
1200KTF7018	N	F1810PM0 filter w/ 1200KTS9075 filter head kit
K1300FA	N	F4030PM0 filter w/ 700ACC7017 filter head kit (Pictured right)



#### Filter Heads

700ACCF7017	N	1"
1200KTS9075	N	3/4"



# FILL-RITE®

## UL LISTED NOZZLES

### Nozzles

Viton seals and O-rings  
Integral hanging hook

Available in 1" and 3/4" NPT



#### 1" Ultra High Flow Automatic Nozzles

Compatible with gasoline, diesel, E15, biodiesel to B20, and kerosene.

N100DAU13	N	Red cover   5-40 GPM (19-150 LPM) (Pictured right)
N100DAU13G	N	Green cover   5-40 GPM (19-150 LPM) (Pictured right)
N100DAU13Y	N	Yellow cover   5-40 GPM (19-150 LPM) (Pictured right)



#### Automatic Nozzles

Compatible with gasoline, diesel, E15, biodiesel to B20, and kerosene.

N100DAU12	N	1"   Red cover   5-25 GPM (19-95 LPM)
N100DAU12G	N	1"   Green cover   5-25 GPM (19-95 LPM)
FRNA100DAU00	NA	1"   Blue cover   5-25 GPM (19-95 LPM) (Rated to -40°F/-40°C)
N075DAU10	N	3/4"   Green cover   2.5-14.5 GPM (9.5-55 LPM) Diesel only
N075UAU10	N	3/4"   Red cover   2.5-14.5 GPM (9.5-55 LPM) Unleaded only
FRNA075DAU10	NA	3/4"   Blue cover   2.5-14.5 GPM (9.5-55 LPM) (Rated to -40°F/-40°C)

#### Manual Nozzles

Compatible with gasoline and diesel

FRHM100S	N	1"   Up to 20 GPM (75 LPM)
FRHM075S	N	3/4"   Up to 20 GPM (75 LPM)

#### Multi-plane Swivels

360° rotation | Rated to -40°F/-40°C



S100H1315	N	1"
S075H1314	N	3/4"

#### Whip Hoses

Resistant to cuts, abrasions, & weather



WH10012	N	1" x 12"   1" x 30.5 cm
WH07509	N	3/4" x 9"   3/4" x 22.9 cm

#### Vent Caps

FRTC	N	Cap only
FRTCB	N	Cap w/ 2" (5 cm) base

#### Breakaways

Non-reconnectable | Instant closing poppet check valve



B100F475	N	1"
B075F530	N	3/4"

#### Suction Pipes

Telescoping suction pipes available in metallic and non-metallic

1200KTS9089	N	Steel   1" x 20" to 34 1/2"   1" x 50.8 cm - 87.6 cm
30F18179	N	Polypropylene   1/2" x 21" to 36"   1/2" x 53.3 cm - 91.4 cm